

CamCleaner 6000



Advantages

- Healthier employees
- Less cleaning
- Eliminates tobacco smoke, weld smoke, construction dust, asbestos and particles of all sizes down to ultrafine.
- Lower energy costs
- Reduced environmental impact
- Clean products, fewer operational disruptions
- Reduces the average temperature in rooms with high ceilings

Applications: Air purifier for dusty environments and large indoor premises such as pharmaceutical facilities, food factories, heavy industry, paper mills, welding workshops, timber facilities, bakeries, packaging production, printing facilities, stables, processing industry, supermarkets and other specialist applications such as upgrading of clean room environments and other classified assembly environments.

Power supply: 3-phase 380-480 V

Frequency: 50Hz

Filter: F7, E11-H13

Fan: FRE vent fan with adjustable rotation speed and pressure

Capacity: 0 - 7500 m³/h

Connection: 4 standard round (diameter 315mm) or 2 standard round (diameter 315mm) and 2 round (diameter 250mm)

Installation: Mobile or stationary, floor, wall or ceiling mounting (with wire or suspension arms). Can be used with Camfil Farr's filter cabinet.

Item no.	Type	Dimensions (WxHxD) mm	Weight kg	Air volume m ³ /h	Initial pressure drop Pa	Air purification area m ²	Noise level dBa	Power output kW at 4000 m ³ /h	Filter included in standard version *
501560	CamCleaner 6000 standing	800x1824x745	90	max 7500	78	max 1000	31-71	0.18	F7/E11
501561	CamCleaner 600 Horizontal	1272x1351x745	90	max 7500	78	max 1000	31-71	0.18	F7/E11

* Other filter classes available on request

Exchange

Item no.	Type	Model	Dimensions (BxHxD) mm	Filter class according to EN779:2002	Number of filters per air purifier	Comments
308012	Main filter	Micretain	MGMM (1220x610x100-01)	E11	2	Standard
301969	Pre-filter	Ecopleat G	3GPF (610x610x50)	F7	4	Standard

* Other filter classes available on request

As part of our continuous improvement, Camfil Farr reserve the right to change specifications without notice.